# **SPEED & PRECISION**





### ProMaker **L6000 D**

WWW.PRODWAYS.COM

#### A SPECIALIZED SOLUTION FOR MANUFACTURING

ProMaker L6000 D was designed for use in industries requiring large-volume production of unique, detailed parts with incredible speed, precision and reliability. The L6000 D features a granite build platform which allows for increased stability and improved productivity by reducing the need for support structures.

#### LOW OPERATING COSTS AND HIGH PERFORMANCE

ProMaker L6000 D features an economical LED light source and experiences minimal wear-an-tear over time, resulting in lower operating costs without sacrificing speed or quality. Compatible with 365-nm UV resins, the L6000 D is capable of efficiently and reliably producing parts for a wide variety of applications.



- Unmatched resolution: less than 40 µm with hundreds of millions of pixels per layer
- High precision: achieve incredibly fine detail over the entire build platform with no distortion
- Unparalleled speed: production up to 10X faster than market standards
- High throughput: achieve high production volumes without sacrificing quality
- Superior surface quality: minimal post-production finishing required
- Lower operating cost: minimal wear-and-tear on machine and less costly LED light source



## ProMaker L6000 D TECHNICAL SPECIFICATIONS

| Net build volume            | 800 x 330 x 200 mm<br>31 x 13 x 8 inches                  |
|-----------------------------|---|
| Number of heads             | 1   |
| Footprint (LxW)             | 3380 x 3140 mm (10.6m²)<br>134 x 124 inches (114 sq. ft.) |
| Native resolution (X, Y, Z) | 605 x 605 x 1016 DPI<br>~40 μm (0.0016 inches)            |
| Layer thickness             | 25 - 150μm<br>0.001 to 0.006 inches                       |
| MOVINGLight® heads          | 1920 x 1080 pixels  |
| Platform                    | Granite   |
| Size (LxWxH)                | 2285 x 1266 x 2230 mm<br>90 x 50 x 88 inches              |
| Weight                      | 1900 Kg<br>4180 lbs.                                      |
| VAT Volume                  | ~125 L<br>33 US Gal                                       |
| Power requirements          | 100 - 127 VAC, 50 A, 60 Hz<br>220 - 240 VAC, 25 A, 50 Hz  |
| Workshop compatibility      | Windows 7/8   |
| Certification               | CE  |
|                             |   |

By choosing one of our ProMaker machines, you're also accessing our vast technical knowledge and a wide range of available services to help optimize production and maximize profitability.

TRAINING • MAINTENANCE • HOTLINE AND ON-SITE ASSISTANCE • SPECIFIC DEVELOPMENT





@prodways

